



US008435035B1

(12) **United States Patent**
Fatiny

(10) **Patent No.:** **US 8,435,035 B1**

(45) **Date of Patent:** **May 7, 2013**

(54) **DENTAL INSTRUMENT**

(75) Inventor: **Fahad Ibrahim Fatiny**, Riyadh (SA)

(73) Assignee: **King Saud University**, Riyadh (SA)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/298,160**

(22) Filed: **Nov. 16, 2011**

(51) **Int. Cl.**
A61C 3/00 (2006.01)

(52) **U.S. Cl.**
USPC **433/149**

(58) **Field of Classification Search** 433/114,
433/141, 143, 144, 145, 149, 25, 34, 37,
433/40, 125, 164, 142, 148, 215, 216; 606/53,
606/79, 84; D24/146, 152, 154, 156, 176;
600/210, 237

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

739,333	A	9/1903	Miles, Jr.	
1,109,924	A	9/1914	Hoffman et al.	
2,056,417	A	10/1936	Bosworth	
2,674,799	A	4/1954	Fraser	
4,270,902	A *	6/1981	Wiland	433/144
4,315,745	A	2/1982	Murata	
4,365,957	A *	12/1982	Das	433/144
4,854,867	A *	8/1989	Meinershagen	433/40
5,830,225	A	11/1998	Detsch	
5,934,905	A *	8/1999	Martoral et al.	433/144
6,309,219	B1	10/2001	Robert	

2005/0095558	A1 *	5/2005	Jones	433/144
2006/0063130	A1 *	3/2006	Hayman et al.	433/141
2006/0160046	A1 *	7/2006	Nesbitt et al.	433/88
2009/0042165	A1	2/2009	Garrison et al.	

FOREIGN PATENT DOCUMENTS

EP	2260787	12/2010
WO	WO 2005/079693	9/2005
WO	WO 2009/118741	10/2009

OTHER PUBLICATIONS

Website, http://www.kabdental.com/small-dental-equipment/miltex_instruments_and_products/elevators.htm, series of dental instruments, 11 pages printed from the internet on Jun. 13, 2011.

* cited by examiner

Primary Examiner — Cris L Rodriguez


Assistant Examiner — Justin O'Donnell

(74) *Attorney, Agent, or Firm* — Richard C. Litman

(57) **ABSTRACT**

The dental instrument is formed of a single elongate, unitary length of surgical steel or other suitable material. The instrument preferably includes two mutually opposed working end portions and a generally medial cushioned handgrip portion. Each of the end portions has a shallow axial channel and a sharpened distal end having a notch formed therein. The two sides of the notch provide two contact points or areas to avoid the extreme pressures applied by conventional single contact point instruments and the resulting breakage of the tooth and subsequent difficulty in extracting the base or root of the tooth that often occurs. A lateral notch having sharpened edges is also preferably formed along one side of each working end portion of the tool. The configuration of the dental instrument provides greater versatility to perform the manipulations generally required for tooth extraction.

5 Claims, 3 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3




Fig. 4

1

DENTAL INSTRUMENT

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to tools, instruments, and implements used in the medical field, and particularly to a manual dental instrument for elevating and luxating or loosening teeth in preparation for extraction.

2. Description of the Related Art

Although modern medical science and technology have greatly improved the ability of dentists and other medical professionals to retain the natural teeth for their patients, from time to time it is still necessary to extract a natural tooth. Such tooth extractions must still be accomplished by hand, using manual tools for the most part. Accordingly, a number of different tools and instruments have been developed in the past, for extracting a tooth or preparing a tooth for extraction.

Most of these instruments used for the preparation of extraction, i.e., luxating or loosening the tooth, are shaped or contoured to provide only a single contact point, or at most a single short line of contact, between the tooth and the instrument. The resulting very high localized pressure can often result in the tooth breaking before the root has been loosened sufficiently to facilitate extraction. When this occurs, the dentist or dental professional is left with a considerably more complex and time-consuming operation to remove the remaining tooth. This additional work results in additional trauma for the patient.

None of the above inventions and patents, taken either singly or in combination, is seen to describe the instant invention as claimed. Thus, a dental instrument solving the aforementioned problems is desired.

SUMMARY OF THE INVENTION

The dental instrument is formed of a single elongate, unitary length of surgical steel or other suitable material. The instrument preferably includes two mutually opposed working end portions and a generally medial cushioned handgrip portion. Each of the end portions has a shallow axial channel with a sharpened distal end having a notch formed therein. The two sides of the notch provide two contact points or areas to avoid the extreme pressures applied by conventional single contact point instruments and the resulting breakage of the tooth and subsequent difficulty in extracting the base or root of the tooth that often occurs. A lateral notch having sharpened edges is also preferably formed along one side of each working end portion of the tool.

The configuration of the dental instrument provides greater versatility to perform the manipulations generally required for tooth extraction. The instrument enables the dental professional to luxate or loosen the subject tooth prior to extraction by prying or levering the tooth angularly, and provides some ability to rotate the tooth axially as well in order to luxate the tooth prior to applying forceps for the actual extraction. The sharpened blades of the distal end notch of the dental instrument also enable the dental professional to cut the tissue surrounding the subject tooth, thereby further facilitating the removal of the tooth.

These and other features of the present invention will become readily apparent upon further review of the following specification and drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a dental instrument according to the present invention, illustrating its general configuration and features.

2

FIG. 2 is a partial detailed top plan view of one of the working end portions of the dental instrument according to the present invention, illustrating further details thereof.

FIG. 3 is an end elevation view of the dental instrument according to the present invention, illustrating further details thereof.

FIG. 4 is an environmental perspective view of the dental instrument according to the present invention, illustrating an exemplary manipulation of the instrument in preparation for the extraction of a tooth.

Similar reference characters denote corresponding features consistently throughout the attached drawings.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The dental instrument enables the dental professional to luxate or loosen a tooth prior to extraction. FIGS. 1 and 4 provide an enlarged perspective view of the dental instrument 10, illustrating its general features. The dental instrument 10 is formed of a rigid, continuous, straight elongate rod of surgical steel or other suitable material, and has a generally medial handle portion 14 and at least one working portion. The embodiment of the instrument 10 shown in FIGS. 1 and 4 includes two mutually opposed working portions 16a and 16b, which are mirror images of one another. Each of the working portions 16a and 16b includes a distal tip 18a and 18b opposite the central handle portion 14.

FIG. 3 of the drawings provides an end elevation view of the first working end 18a of the dental instrument 10. This end elevation view shows that the rod or shank of the tool 10 has a generally elliptical cross section, having a major diameter 20. Each working portion of the rod 12 is formed with a shallow channel therein that extends from adjacent the handle portion 14 to the tip of the respective working portion, e.g., the channel 22a of the working portion 16a of the tool 10 as shown in FIG. 3, with the opposite working portion 16b having a corresponding shallow channel 22b, as shown in FIG. 1. The channel 22a is defined by its mutually opposed, coplanar and parallel channel edges 24a and 26a, and the opposite channel 24a has a similar configuration defined by its channel edges 24b and 26b. Each of the channel edges comprises a flat surface. The planes forming the two flat surfaces of each channel edge pair, e.g., channel edges 24a and 26a, are coplanar with one another.

The tip 18a, 18b of each working portion 16a, 16b is formed with a notched and sharpened edge, respectively 28a and 28b. The notches preferably define an included angle A of about 135°, as shown most clearly in the top plan view of the working portion 16a of the instrument 10 in FIG. 2. Other notch angles may be provided. The notched tips 18a, 18b of the instrument 10 are beveled. The beveled surfaces 30a, 32a and 30b, 32b result in the sharpened cutting edges 28a and 28b for the notched tips 18a and 18b. In addition, one of the channel edges of each working portion 16a and 16b may include a notch therein, as shown by channel edge notch 34a of the first channel edge 24a of the first working portion 16a and channel edge notch 34b of the first channel edge 24b of the second working portion 16b. The configurations of the two channel edge notches 34a and 34b are similar to the two notched tips 18a and 18b of the two working portions 16a, 16b of the tool 10. The first working portion channel edge notch 34a has first and second beveled surfaces 36a and 38a, and the second working portion channel edge notch 34b has first and second beveled surfaces 36b and 38b to form their respective sharpened edges. The included angle A of the two channel edge notches 34a and 34b is preferably about 135°, as

3

shown for the channel edge notch **34a** in the plan view of FIG. 2. The channel edge sharpened notches **34a** and **34b** provide additional flexibility in the use of the dental instrument **10** in prying or otherwise luxating a tooth in preparation for its extraction.

The dental instrument **10** is formed with a series of convex and mutually adjacent knobs **40** disposed axially therealong and surrounding the medial handle portion **14** of the instrument **10**. The knobs **40** preferably increase in diameter from the first knob adjacent the respective working end **16a** and **16b** of the instrument **10** to a medial largest diameter knob. Each of the knobs **40** has a circular cross section that is somewhat larger than the major diameter **20** of the elliptical cross section of the working portion of the instrument **10**, as shown in the end view of FIG. 3. A resilient handgrip **42** is molded or otherwise formed over the knobs **40** of the medial portion **14** of the instrument **10**. The handgrip **42** material preferably comprises a pliable material having a high surface coefficient of friction, e.g., Neoprene® or other suitable material having similar properties. The resilient material of the handgrip **42** is preferably molded or otherwise formed to conform to the different diameters of the underlying knobs **40** in order to provide a good grip for the dentist or dental professional using the instrument **10**.

FIG. 4 of the drawings provides an illustration of the dental instrument **10** as it might be used for luxating a tooth T in preparation for extraction of the tooth. The tip **18b** of the first working end **16b** may be worked alongside the subject tooth T, or perhaps levered between adjacent teeth as a result of the relatively thin material defining the channel **22a**. The opposite working end **16a** may be used in a similar manner, as desired. The instrument **10** may be worked around the tooth T to loosen the tooth within its socket. The two beveled surfaces **30a** and **32a** (shown in FIGS. 1 through 3) result in two contact points or lines across the beveled surfaces to greatly reduce point pressure on the tooth. This greatly reduces the chances of the tooth T fracturing across its diameter, and the subsequent need to remove the base of the tooth from the socket and the accompanying difficulties and additional trauma that such a procedure entails for the patient. Accordingly, the dental instrument **10** will serve to facilitate and ease the procedure of luxating a tooth in preparation for its extraction during dental procedures.

4

It is to be understood that the present invention is not limited to the embodiments described above, but encompasses any and all embodiments within the scope of the following claims.

I claim:

1. A dental instrument for luxating and axially rotating a tooth, comprising a rigid, elongate, rod having:
a handle portion, the handle portion having opposing ends; mutually opposed first and second working portions in mirror image to one another and located on respective opposing ends of the handle portion, each of the working portions including a distal tip opposite the handle portion and a generally elliptical cross section defining a major axis, the elliptical cross section further defining a shallow channel formed along the working portion and extending to the distal tip, the channel being defined by a first and second channel edge, wherein the first and second channel edges are mutually opposed, coplanar, and coincident with the major axis of the elliptical cross section; and

the tip has a single notched and sharpened edge subtending an included obtuse angle extending between the first and second channel edges, wherein the first channel edge includes a sharpened notch therein and the second channel edge has a straight length extending from the handle portion to the distal tip, wherein the first and second channel edges of the channel comprise coplanar flat surfaces spaced rearwardly away from the distal tip.

2. The dental instrument according to claim 1, wherein said handle portion being disposed medially between the first and second working portions, the handle portion having a plurality of mutually adjacent knobs disposed axially therealong, each of the knobs having a circular cross section of larger diameter than the major axis of the working portions, each of the knobs surrounding the handle portion, the handle portion further comprising a resilient handgrip disposed over the handle portion, the resilient handgrip having an exterior configuration generally conforming to the configuration of the underlying handle portion.

3. The dental instrument according to claim 1 further comprising a resilient handgrip disposed over the handle portion.

4. The dental instrument according to claim 1, wherein the rod is formed of surgical steel.

5. The dental instrument according to claim 1 wherein the obtuse angle is about 135°.

* * * * *